

CONTEC

CMS6500 Vital signs monitor



CONTEC

Features

- 7" TFT, touch screen, led backlight, 800x480 pixels.
- Vistual and Audio alarms, adjustable.
- Patient managment, name and age and id.
- Network with Central Station Software
- Audio volume ajustable form 1 ~ 8 level.
- Multi-language options: Germany, France, Italian, Turkey, etc
- Built-in removable and rechargeable lithium battery
- UI with both Keypad and Touch Screen operation.
- Memory: Built-in memory or miniSD Memory card. Store more than 1000 pieces of archive
- Powerful data storage and managment, Trend graph, Trend table, etc.
- Arrythmia analysis and S-T segment analysis.

Specifications

ECG

■ Lead mode: 3-lead or 5-lead

■ HR range: 15 ~ 300 bpm

■ Accuracy: ±2bpm or ±2%, which is greater

NIBP

■ Method: Oscillometry

■ Mode: Manual/Auto/Contiuous

■ Measurement Range: 25 ~ 260mmHg

SpO₂

■ Measurement Range: 0 ~ 100%

■ Accuracy: ±2%(70%~100%); 0% ~ 69% unspecified

Pulse Rate

■ Measurement Range: 25 ~ 250 bpm

■ Accuracy: ±3 bpm

■ Dimension: 191 x 160 x 244 (mm)

■ Net wight: 2.1KG

Optional

■ RESP, 2-TEMP, 2-IBP, ETCO2,Wifi

Илан Медицинска Апаратура ООД

гр. Варна, ул. Кирил Шиваров 9 Б тел. **0700 17373**

факс 052 612258 e-mail: office@ilan.bg www.llan.bg

CMS6500

