



CONTEC®



CMS7000

Multi-parameter Monitor

ECG

- Lead type: 5-lead
- Input: RA; LA; RL; LL; V
- Sweep speed: 12.5mm/s, 25mm/s, 50mm/s
- Accuracy: $\pm 1\text{bpm}$ or $\pm 1\%$, which is greater
- Protection: Withstand 4000VAC/50Hz voltage in isolation against electrosurgical and defibrillation
- S-T detection: YES, Arrhythmia analysis: YES
- Alarm: YES, audible and visual alarm, alarm events recallable

Standard Configuration

- ECG, NIBP, SPO2
- 12.1"color TFT display
- Suitable for adult, pediatric and neonatal patient
- Basic parameters (ECG, SPO2, NIBP) in a durable case for bedside monitoring and transport monitoring
- Audible and visual alarms with adjustable alarm ranges
- Networkable with CONTEC central monitoring system
- Powerful data management and storage capacity

NIBP

- Method: Oscillometry
- Operation modes: Manual/Automatic/STAT
- Measurement unit: mmHg/KPa selectable
- Measurement types: Systolic, Diastolic, Mean
- Over-pressure protection: YES

SPO2

- Measurement range: 0~100%
- Accuracy: $\pm 2\text{digit}$ (70~100%);
- 0~69% unspecified

Optional

- RESP,2-TEMP,2-IBP,ETCO2,Network,Thermal Printer,Pace Maker



CMS7000

Option



EtCO₂ MODULE (Side stream)



IBP MODULE



EtCO₂ Sampling Cube



IBP Transducer



PRINTER



IBP Cable

Илан Медицинска Апаратура ООД
гр. Варна, ул. Кирил Шиваров 9 Б
тел. **0700 17373**
факс 052 612258
e-mail: office@ilan.bg
www.ilan.bg